

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (currently amended) A method for generating parametric output from a parametric loudspeaker system, comprising the steps of:
retrieving a pre-encoded audio signal from an electronically readable, optical storage medium with ultrasonic bandwidth, wherein an ultrasonic carrier signal having at least one sideband represents the pre-encoded audio signal; and
playing back the pre-encoded audio signal through an ultrasonic amplifier and emitter.
2. (previously presented) A method as in claim 1, wherein retrieving a pre-encoded audio signal further comprises the step of retrieving the pre-encoded audio signal which has been pre-processed.
3. (previously presented) A method as in claim 2, further comprising the step of retrieving the pre-encoded audio signal which has been pre-processed with distortion error correction.
4. (original) A method as in claim 1, further comprising the step of modulating the ultrasonic carrier signal with the audio signal to produce the pre-encoded audio signal.
5. (canceled).
6. (original) A method as in claim 1, further comprising the step of retrieving a processed audio signal from a magnetic storage medium with ultrasonic bandwidth.
7. (original) A method as defined in claim 1, comprising of the further steps of:

positioning the parametric loudspeaker system with a projection orientation toward an intended listening area; and
playing back the pre-encoded audio signal in a region substantially limited to the intended listening area.

8. (currently amended) A method for storing parametric output for later playback from a parametric loudspeaker system, comprising the steps of:
modulating an ultrasonic carrier with an audio signal to create a modulated signal comprising the ultrasonic carrier signal and at least one sideband signal;
producing a processed signal that represents the modulated signal; and
storing the processed signal on an electronically readable storage medium;
wherein the step of modulating the ultrasonic carrier further comprises the step of applying distortion error correction to the audio signal to produce the processed signal.

9. (canceled).

10. (previously presented) A method as in claim 8, further comprising the step of playing back the processed signal from the electronically readable storage medium through an ultrasonic amplifier and emitter.

11. (currently amended) A device for storing parametric audio signals for output through a parametric loudspeaker system, comprising:
an electronically readable storage medium;~~and~~
an ultrasonic carrier signal having at least one sideband which represents a pre-encoded audio signal, wherein said pre-encoded audio signal is stored on the electronically readable storage medium; and
an error correction module to pre-distort the modulated signal and form a processed signal.

12. (original) The device as in claim 11, further comprising:

a retrieval unit for retrieving a pre-encoded audio signal from an electronically readable storage medium that has ultrasonic bandwidth; and
a playback module for playing back the pre-encoded audio signal.

13. (original) The device as in claim 12, wherein the playback module further comprises:
an amplifier, coupled to the retrieval unit, for amplifying the pre-encoded ultrasonic signal; and
an ultrasonic emitter, coupled to the amplifier, configured to emit ultrasonic waves that de-couple in the air to audible sounds.

14. (previously presented) The device as in claim 11, further comprising a recording module for recording the pre-encoded audio signals onto the electronically readable storage medium, the recording means comprising:
a modulator, configured to pre-encode an ultrasonic carrier signal with the audio signal to form a processed signal; and
a write unit configured to write the processed signal to an electronically readable storage medium for replay by the parametric loudspeaker system.

15. (canceled).

16. (currently amended) The device as in claim 11~~claim 15~~, further comprising a compression module to compress the modulated signal and form a compressed signal.

17. (previously presented) A method for storing pre-encoded signals for a parametric loudspeaker system, comprising the steps of:
receiving at least one audio signal;
modulating an ultrasonic carrier signal with the audio signal to form a modulated signal comprising the ultrasonic carrier signal and at least one sideband signal;
applying error correction to the modulated signal to form a processed signal; and

storing the processed signal on an electronically readable storage medium for replay by the parametric loudspeaker system.

18. (original) A method as in claim 17, further comprising the step of storing the processed signal on an optical storage medium with an ultrasonic bandwidth.

19. (original) A method as in claim 17, further comprising the step of storing the processed signal on a magnetic storage medium with an ultrasonic bandwidth.

20. (original) A method as in claim 17, further comprising the step of storing the processed signal on a high bandwidth storage medium with an ultrasonic bandwidth.

21. (original) A method as in claim 17, wherein the step of applying error correction further comprises the step of applying error correction to correct for distortion introduced in the parametric demodulation process in air.

22. (previously presented) A method for generating parametric output through a parametric loudspeaker system, comprising the steps of:
receiving an incoming audio signal;
modulating an ultrasonic carrier signal with the audio signal to form a modulated signal comprising the ultrasonic carrier signal and at least one sideband signal;
applying error correction to the modulated signal to form a processed signal;
storing the processed signal on an electronically readable storage medium; and
playing back the processed signal through an ultrasonic amplifier and emitter.

23. (original) A method as in claim 22, further comprising the step of storing the processed audio signal on an optical storage medium with an ultrasonic bandwidth.

24. (previously presented) A method as in claim 22, further comprising the step of

storing the processed audio signal on a Super Audio Compact Disk (CD).

25. (original) A method as in claim 22, further comprising the step of storing the processed audio signal on a magnetic storage medium with an ultrasonic bandwidth.

26. (original) A method as in claim 25, further comprising the step of storing the processed audio signal on a hard drive used as the magnetic storage medium.

27. (original) A method as in claim 22, further comprising the step of playing back the processed audio signal through an ultrasonic emitter having a film diaphragm.

28. (canceled).

29. (previously presented) A device to store pre-encoded signals for a parametric loudspeaker system, comprising:
an audio signal;
a modulator configured to modulate an ultrasonic carrier signal with the audio signal to produce a modulated signal comprising the ultrasonic carrier signal and at least one sideband signal;
an error correction unit configured to pre-correct the modulated signal for de-modulation distortion created by demodulation of parametric output in air; and
an electronically readable storage medium, having an ultrasonic bandwidth, configured to store the pre-corrected, modulated signal.

30. (previously presented) A method for pre-encoding signals for a parametric loudspeaker system through a computer network, comprising the steps of:
receiving an incoming audio signal at a network processing node;
processing an ultrasonic carrier signal with the audio signal using a computer to form a modulated signal comprising the ultrasonic carrier signal and at least one sideband ; and

transmitting the modulated signal through the computer network for replay by the parametric loudspeaker system.

31. (original) A method as in claim 30, further comprising the step of applying error correction to the modulated signal to form a processed signal.

32. (previously presented) A method as in claim 31, further comprising the step of transmitting the processed signal through the computer network for storage on an electronically readable storage medium.

Claims 33-37 (canceled).

38. (original) A device for storing parametric audio signals for output through a parametric loudspeaker system, comprising:
an electronically readable storage medium having an audible bandwidth storage capacity; and
a pre-distorted audio signal, having distortion error correction applied thereto, stored on the electronically readable storage medium.

39. (previously presented) A method for generating parametric output from a parametric loudspeaker system, comprising the steps of:
retrieving a pre-distorted audio signal from an electronically readable storage medium for storing an audible audio bandwidth;
modulating an ultrasonic carrier signal with the pre-distorted audio signal to form a pre-encoded audio signal comprising the ultrasonic carrier signal and at least one sideband signal ; and
playing back the pre-distorted audio signal through an ultrasonic amplifier and emitter.

40. (original) A method as in claim 39, wherein the step of modulating further comprises the step of modulating the retrieved signal using a switching modulator before playback.

41. (original) A method as in claim 39, wherein the switching modulator further comprises a phase shifter and a quadrature modulator.

42. (previously presented) A method for generating parametric output through a parametric loudspeaker system, comprising the steps of:
receiving an incoming audio signal;
applying error correction to the audio signal to form an error corrected signal;
storing the error corrected signal on an electronically readable storage medium having an audible bandwidth;
retrieving the error corrected signal from the electronically readable storage medium;
modulating an ultrasonic carrier signal with the error corrected signal to form a modulated signal comprising the ultrasonic carrier signal and at least one sideband signal ; and
playing back the modulated signal through an ultrasonic amplifier and emitter.

43. (original) A device for storing parametric audio signals for output through a parametric loudspeaker system, comprising:
an electronically readable storage medium having an audible bandwidth storage capacity;
and
a pre-distorted audio signal, having distortion error correction, ultrasonic modulation and signal compression applied thereto, stored on the electronically readable storage medium.

44. (original) A device as in claim 43, wherein the signal compression compensates for spectrum expansion associated with ultrasonic modulation and allows the audio signal to be stored on the electronically readable storage medium.

45. (original) A device as in claim 43, wherein the signal compression samples a modulated signal at twice an audio sampling frequency and stores alternate samples on two channels of the electronically readable storage medium.

46. (previously presented) A device as in claim 43, wherein the signal compression samples a modulated signal at 88.2 kHz and stores alternating samples on two channels of a CD.

47. (original) A device as in claim 43, wherein the signal compression is a lossy compression format.

48. (original) A device as in claim 43, wherein the signal compression is a lossless compression format.

49. (original) A method for generating parametric output from a parametric loudspeaker system, comprising the steps of:
retrieving a pre-processed audio signal from an electronically readable storage medium for storing an audible audio bandwidth, wherein the pre-processed audio signal has been distortion error corrected, modulated by an ultrasonic carrier, and compressed;
uncompressing the pre-processed audio signal; and
playing back the pre-encoded audio signal through an ultrasonic amplifier and emitter.

50. (original) A method as in claim 49, further comprising the step of uncompressing the pre-processed audio signal that has been compressed to compensate for spectrum expansion associated with modulation by an ultrasonic carrier.

51. (original) A method for generating parametric output through a parametric loudspeaker system, comprising the steps of:
receiving an incoming audio signal;
applying error correction, ultrasonic modulation, and compression to the audio signal to form an error corrected signal;
storing the error corrected signal on an electronically readable storage medium having an audible bandwidth;
retrieving the error corrected signal from the electronically readable storage medium; and

playing back the modulated signal through an ultrasonic amplifier and emitter.